

CERTIFICATE

No. U6 088072 0037 Rev. 00

Holder of Certificate: **AOK Industrial Company Limited**
East Seat, Three Floor Building One
Shengzuozhi Science and Technology Industrial Park
Xinyu Road North Side, Shajing Street
Baoan District
518000 Shenzhen, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **LED Luminaires**
(LED High Bay Light)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142195014701

Date, 2020-07-16



(Taylor Yao)

CERTIFICATE

No. U6 088072 0037 Rev. 00

Model(s):

AOK-300WoFU-NVY-L5-00-XX70-BN-P;
 AOK-400WoFU-NVY-L5-00-XX70-BN-P;
 AOK-460WoFU-NVY-L5-00-XX70-BN-P;
 AOK-500WoFU-NVY-L5-00-XX70-BN-P;
 AOK-600WoFU-NVY-L5-00-XX70-BN-P;
 AOK-300WoFU-NVY-L5-00-XX80-BN-P;
 AOK-400WoFU-NVY-L5-00-XX80-BN-P;
 AOK-460WoFU-NVY-L5-00-XX80-BN-P;
 AOK-500WoFU-NVY-L5-00-XX80-BN-P;
 AOK-600WoFU-NVY-L5-00-XX80-BN-P;
 AOK-750WoFS-NVY-L5-00-XX70-BN-P;
 AOK-960WoFS-NVY-L5-00-XX70-BN-P;
 AOK-750WoFS-NVY-L5-00-XX80-BN-P;
 AOK-960WoFS-NVY-L5-00-XX80-BN-P
 ('XX' can be 27-50, stands for LED CCT, e.g. 27=2700K, 50=5000K; 'BN' can be 15, 30, 60, 90, stands for beam angle of LED lens, e.g. 15=15°, 90=90°, 'P' can be A, B, C, stands for different mounting brackets, A=Yoke mounting bracket; B=Yoke mounting bracket with angle marking; C=Ceiling mounting bracket)

Brand Name:

AOK



Parameters:

Rated Voltage : 100-240VAC
 Rated Frequency : 50/60Hz
 Rated Power : See below table for details
 Protection Class : I
 Degree of Protection : IP66
 Blue Light Risk Group : RG1
 ta : 40 °C

CERTIFICATE

No. U6 088072 0037 Rev. 00

Model No.	Rated Power (W)
AOK-300WoFU-NVY-L5-00-XX70-BN-P	300
AOK-400WoFU-NVY-L5-00-XX70-BN-P	400
AOK-460WoFU-NVY-L5-00-XX70-BN-P	460
AOK-500WoFU-NVY-L5-00-XX70-BN-P	500
AOK-600WoFU-NVY-L5-00-XX70-BN-P	600
AOK-300WoFU-NVY-L5-00-XX80-BN-P	300
AOK-400WoFU-NVY-L5-00-XX80-BN-P	400
AOK-460WoFU-NVY-L5-00-XX80-BN-P	460
AOK-500WoFU-NVY-L5-00-XX80-BN-P	500
AOK-600WoFU-NVY-L5-00-XX80-BN -P	600
AOK-750WoFS-NVY-L5-00-XX70-BN-P	750
AOK-960WoFS-NVY-L5-00-XX70-BN-P	960
AOK-750WoFS-NVY-L5-00-XX80-BN-P	750
AOK-960WoFS-NVY-L5-00-XX80-BN-P	960

**Tested
according to:**

EN 60598-2-1:1989
 EN 60598-2-5:2015
 EN 60598-1:2015/A1:2018

**Production
Facility(ies):**

088072